

ASME Tank Dolly

EZTC717 ASME Tank Dolly

Transports ASME Residential Storage Tanks



The EZTC717 has been totally redesigned in order to accommodate the needs of a changing industry. Set any size ASME tank up to 1,000-gallons with one operator and a utility trailer.



Gone is the conventional transmission and dual drive wheels. This is 100% hydraulic drive. The HONDA® GXV390 13 HP OHV, gasoline engine provides ample power to the pump. A tethered kill switch, which attaches to the operators wrist, provides an added measure of safety. If operator loses control of the

Today, vehicles and support equipment need to be lighter, compact and more efficient. The EZTC717 ASME Tank Dolly provides a safe and efficient platform from which to deliver any size residential propane storage tank, up to 1,000-gal.

This dolly utilizes a Hydro-Gear® hydrostatic pump (PG/PE) and a Sauer Danfoss® orbital hydraulic motor (OMS 400). Together they provide forward and reverse motion to the single drive wheel.

Specifications

Engine: HONDA® GXV390 13 HP, electric start, gas

Hydraulics: Danfoss® 400cc OMSW hydraulic motor, Hydro-Gear® hydraulic pump

Weight: 716 lbs.

Capacity: 2,300 lbs. (1,000-gal. propane tank with 5%)

Dimensions: 58 in. (h) x 60 in. (w) x 82 in. (d)

Construction: 100% aluminum

Straps: (1) 3 in. X 13 ft. nylon (20,000 lbs. breaking strength) 806 ratchet, (2) 2 in. X 13 ft. nylon (10,000 lbs. breaking strength)

Tires: (3) 23/850-12 Carlisle Super Lug 2-ply Bar tires

Assembly: No assembly required

Warranty: One year on structural defects.

Shipping: Common Carrier, LTL

Shipping Dimensions: 64 in. (h) x 40 in. (w) x 88 in.



unit, falls, or becomes disabled in any way the kill switch is activated stopping the unit in its tracks. A thumb control on the handle bar allows the operator to control the direction of the unit without ever removing his hands from the steering handle, allowing for greater safety and control of the dolly.

